2011 CAMCORDER HDC-SD80 High Definition Camcorder



33.7MM WIDE-ANGLE LENS WITH 37X OPTICAL AND 42X INTELLIGENT ZOOM

Allows you to adapt to a range of shooting situations with the use of wide angle and long zoom.

1080 FULL HD

Record clearly defined images of moving objects.

HYBRID O.I.S. WITH ACTIVE MODE

Minimizes the effects of hand shake for virtually blur-free close-ups and long-zoom shots.

- Zoom Microphone/Wind Noise Canceller
- 2.7" LCD Touch Panel

















2011 CAMCORDER HDC-SD80 High Definition Camcorder

GENERAL			
Power Supply (Battery / AC Adapter)		DC3.6V / 5.0V	
Power Consumption		Max. 4.4W (Recording) / Max. 7.7W (Charging)	
Weight (w/o Battery)		Approx. 0.42lb (192g)	
Dimension (W x H		2.02 x 2.32 x 4.29 [in] (51.5 x 59.0 x 109.0 [mm])	
Media		SD/ SDHC/ SDXC Memory Card	
On-Screen Display Language		Please refer to "OSD" sheet	
IMAGE SENSOR	Language	1.0000 10.00 10 0000	
Image Sensor		1/5.8" MOS	
Total Pixels		1.50 megapixels	
Effective Pixels	Motion Image	1.12 megapixels – 1.30 megapixels [16:9]	
	Still Image	1.10 megapixels [3:2] 1.12 megapixels – 1.30 megapixels [16:9] 0.97 megapixels [4:3]	
LENS SECTION			
Lens Brand		Panasonic Lens	
F Value		F1.8 (WIDE) / 4.0 (TELE)	
Optical Zoom		34X	
Focal Length		2.38 - 81.0 mm	
35mm Film Came	ra Equivalent	33.7 - 1240 mm (16:9) [Motion Image]	
		38.1 - 1298 mm (3:2), 33.7 - 1240 mm (16:9), 41.3 - 1405 mm (4:3) [Still Image]	
Filter Diameter		_	
CAMERA SECTION			
Standard Illumination		1400 lx	
Minimum Illumination		7.0 lx (1/25 Low Light Scene Mode) 1 lx (Color Night View)	
Image Stabilizer		HYBRID O.I.S. [Optical Image Stabilizer]	
Focus		Auto / Manual	
White Balance		Auto / Indoor1 / Indoor2 / Sunny / Cloudy / White Set	
Shutter Speed	Motion Image	[60i] Auto Slow Shutter ON: 1/30 - 1/8000 OFF: 1/60 - 1/8000	
	Still Image		
Iris		Auto / Manual	
Zoom	Intelligent Zoom OFF	37X	
	Intelligent Zoom	42X	
	Digital Zoom	90X/2000X (The maximum value of zoom magnification)	
Backlight Compensation		Yes	
MONITOR			
EVF		-	
Monitor (LCD)		2.7" Wide LCD (230,400 dots)	
STILL IMAGE SECTION Recording Format		JPEG	
Recording Format Recording Image Size	Still Picture	2.6 megapixels (1856 x 1392), 0.3 megapixels (640 x 480) [4:3] 2.8 megapixels (2064 x 1376) [3:2] 3.0 megapixels (2304 x 1296), 2.1 megapixels (1920 x 1080) [16:9]	
	Simultaneous Recording	3.0 megapixels (2304 x 1296), 2.1 megapixels (1920 x 1080) [16:9]	
	Creating Still Picture From Motion Picture	2.1 megapixels (1920 x 1080) [16:9]	
Flash		Yes (Photo Light)	
DPOF		Max. 999 images	

RECORDING SECTION			
Signal System	1080 / 60i, 480 / 60i		
Recording Format	MPEG4-AVC/ H.264 (AVCHD standard compliant) iFrame: MPEG-4 AVC/ H.264 (MPEG-4 AVC file format compliant (.MP4))		
Recording / Playback Mode	HA (17Mbps / VBR), (1920 x 1080) HG (13Mbps / VBR), (1920 x 1080) HX (9Mbps / VBR), (1920 x 1080) HE (5Mbps / VBR), (1920 x 1080) iFrame (28Mbps / VBR), (960 x 540)		
Audio Recording System	Dolby Digital (2ch) iFrame: AAC (2ch)		
Microphone	2ch Stereo, Zoom Microphone		
Speaker	Dynamic Type		
Media Remaining Indication	Yes		
INTERFACES			
AV	-		
HDMI	Yes (mini)		
Microphones (stereo mini)	-		
Headphone (stereo mini)	-		
USB	2.0 Hi-Speed		
AV Multi	Yes		
OTHERS			
LED Video Light	Yes		
Accessory Shoe	-		
STANDARD ACCESSORIES			
AC Adapter	Yes		
AC Cable	Yes		
DC Cable	Included AC Adapter		
Rechargeable Battery Pack	Min. 1790 mAh / Lithium-lon		
AV Multi Cable	Yes		
AV Cable	-		
IR Remote	-		
Shoe Adapter	-		
USB Cable	Yes		
SD Memory Card	-		
Included Software	HD Writer AE 3.0		
Lens Hood	-		
Stylus Pen	Yes		



